

PRO XXS

NEW
to our product range



Art. no.	Name	Assembly height [cm]	Load-bearing capacity*	PU
954020	PRO XXS	1,0 - 1,5	4,0 kN	50

The PRO XXS comes with both an L-adapter and stone adapter.
The adjustable foot XXS can be combined with up to two extension plates XXS for height expansion.
Please note: The adapters for the XXS adjustable pedestal are only suitable for the XXS and cannot be combined with the rest of the PRO family.

XXS extension plate

NEW
to our product range



Art. no.	Name	Assembly height [cm]	Load-bearing capacity*	PU
954021	XXS extension plate	0,5	4,0 kN	50

PRO XS / PRO S

NEW
to our product range
PRO XS



Art. no.	Name	Assembly height [cm]	Load-bearing capacity*	PU
954061	PRO XS	2,2 - 3,0	8,0 kN	20
946070	PRO S	3,0 - 5,3	8,0 kN	10

The PRO XS comes with both an L-adapter and stone adapter.
PRO S: Height adjustable in 3 stages of 5 mm each and an additional 8 mm can be combined with the thread.
Please note: The adapters for the XS adjustable pedestal are only suitable for the XS and cannot be combined with the rest of the PRO family.

基座PRO XXS

架高高度: 1,0-1,5公分

可乘載重量: 4,0kN

PRO XXS系列含有XXS專用的L接合器(用於鋁框或木板)和石板接合器

PRO XXS可跟XXS延伸片做搭配調整高度, 最多可裝兩片

注意: XXS的接合器只能用於XXS架高器, 不能與其他共用!

XXS延伸片

架高高度: 0,5公分

可乘載重量: 4,0kN

基座PRO XS

架高高度: 2,2-3,0公分

可乘載重量: 8,0kN

PRO XS系列含有XS專用的L接合器(用於鋁框或木板)和石板接合器

注意: XS的接合器只能用於XS架高器, 不能與其他共用!

可調整自平式基座SL PRO M

架高高度: 5,5-8,4公分

可乘載重量: 8,0kN

傾斜度可達8%

*調整高度時應配上接合器一起調整

可調整自平式基座SL PRO L

架高高度: 7,3-10,2公分

可乘載重量: 8,0kN

傾斜度可達8%

*調整高度時應配上接合器一起調整

*基座底部可依標示記號裁切

SL PRO M

NEW
to our product range



Art. no.	Name	Assembly height [cm]*	Load-bearing capacity	PU
946071-SL	SL PRO M	5,5 - 8,4	8,0 kN	10

* The adapter must be attached to produce an assembly height in the adjustment range!

SL PRO L

NEW
to our product range



Art. no.	Name	Assembly height [cm]*	Load-bearing capacity	PU
946072-SL	SL PRO L	7,3 - 10,2	8,0 kN	10

* The adapter must be attached to produce an assembly height in the adjustment range!



